Fits Your Needs Unique Features of the AS720 **Tank Capacity** 750 gallons **Transmission** JCB transmission Power Shift, 4-speed **Engine** Tier 3 160 hp Cummins engine **Top Road Speed** 28 MPH Weight 19,200 lbs (approx. dry weight) **Crop Clearance** 42" with JCB planetary final drives 50" clearance with 18" drop box all-gear final drives (optional)

APACHE JET

to read more about the AS720 go to: ETsprayers.com/AS720





Unique Features of the AS720

Tank Capacity

750 gallons

Transmission

JCB transmission Power Shift, 4-speed

Engine

Tier 3 160 hp Cummins engine

Top Road Speed

28 MPH

Weight

19,200 lbs (approx. dry weight)

Crop Clearance

42" with JCB planetary final drives 50" clearance with 18" drop box all-gear final drives (optional)



Standard Features

COMMON FEATURES FOR ALL APACHE MODELS

ENGINE & DRIVE TRAIN	FUEL CAPACITY	100 gallons
CHASSIS, SUSPENSION & TIRES	SUSPENSION	Patented independent hydraulic
	BRAKES	Fully enclosed, self-adjusting, internal wet disc brakes
	FRONT TIRES	380/80R38 (narrow and semi-float options available)
	REAR TIRES	380/90R46 (narrow, semi-float, and full-float options available)
	TRANSPORT WIDTH AND HEIGHT	144" maximum
<u>ਂ</u>	OVERALL LENGTH	290" maximum
SPRAY OPTIONS	BOOMS	Ст сиэтом воом Straight 80', 90' or 100'; combo 60'/80' or 60'/90' Straight 120' or 132'
	PRODUCT PUMP	HYPRO,® Hydraulically-driven centrifugal product pump
	RINSE TANK	100 gallons
CAB	ET CUSTOM PRESSURIZED	State-of-the-art cab interior and console (pages 6-9)

PRECISION APPLICATION EQUIPMENT AVAILABLE FACTORY-INSTALLED ON ALL NEW APACHES BY RAVEN AND Trimble.

All Model Year 2015 Apache Sprayers are available with optional ISOBUS-ready wiring in lieu of factory-installed field computers. Refer to your specific precision agriculture product documentation for compatibility information. Equipment Technologies factory installs all field computers using CAN bus wiring and protocols.

