

Ultimate Horsepower

Plus II

Unique Features of the AS1020 Plus II

Tank Capacity

1,000 gallons

Transmission

ZF Power Shift, 6-speed
with lock-up torque converter

Engine

Tier 3 275 hp
Cummins engine

Top Road Speed

35 MPH

Weight

20,265 lbs (approx. dry weight)

Crop Clearance

50" clearance with 18" drop box
all-gear final drives
(Required with Plus II package)

Unique Features of the AS1220 Plus II

Tank Capacity

1,200 gallons

Transmission

ZF Power Shift, 6-speed
with lock-up torque converter

Engine

Tier 3 275 hp
Cummins engine

Top Road Speed

35 MPH

Weight

20,300 lbs (approx. dry weight)

Crop Clearance

50" clearance with 18" drop box
all-gear final drives



APACHE by **ET**
SPRAYERS

to read more about the Plus II
go to: ETsprayers.com/Plus2



Plus II

Unique Features of the AS1020 Plus II

Tank Capacity

1,000 gallons

Transmission

ZF Power Shift, 6-speed
with lock-up torque converter

Engine

Tier 3 275 hp
Cummins engine

Top Road Speed

35 MPH

Weight

20,265 lbs (approx. dry weight)

Crop Clearance

50" clearance with 18" drop box
all-gear final drives
(Required with Plus II package)

Unique Features of the AS1220 Plus II

Tank Capacity

1,200 gallons

Transmission

ZF Power Shift, 6-speed
with lock-up torque converter

Engine

Tier 3 275 hp
Cummins engine

Top Road Speed

35 MPH

Weight

20,300 lbs (approx. dry weight)




Crop Clearance

50" clearance with 18" drop box
all-gear final drives



Standard Features

COMMON FEATURES FOR ALL APACHE MODELS

ENGINE & DRIVE TRAIN	FUEL CAPACITY	100 gallons
	SUSPENSION	Patented independent hydraulic
CHASSIS, SUSPENSION & TIRES	BRAKES	Fully enclosed, self-adjusting, internal wet disc brakes
	FRONT TIRES	 380/80R38 (narrow and semi-float options available)
	REAR TIRES	 380/90R46 (narrow, semi-float, and full-float options available)
	TRANSPORT WIDTH AND HEIGHT	144" maximum
	OVERALL LENGTH	290" maximum
SPRAY OPTIONS	BOOMS	 Straight 80', 90' or 100'; combo 60'/80' or 60'/90' Straight 120' or 132'
	PRODUCT PUMP	HYPRO [®] Hydraulically-driven centrifugal product pump
	RINSE TANK	100 gallons
CAB	ET CUSTOM PRESSURIZED	State-of-the-art cab interior and console (pages 6-9)

PRECISION APPLICATION EQUIPMENT AVAILABLE FACTORY-INSTALLED ON ALL NEW APACHES BY  AND .

All Model Year 2015 Apache Sprayers are available with optional ISOBUS-ready wiring in lieu of factory-installed field computers. Refer to your specific precision agriculture product documentation for compatibility information. Equipment Technologies factory installs all field computers using CAN bus wiring and protocols.

APACHE by **ET**
SPRAYERS

800-861-2142
ETsprayers.com